

SPECIFICATIONS

SMART THERMOSTAT

Important: A home Wi-Fi Internet connection is required to get the most out of this product.

Installation of the product by a professional is recommended.

Netatmo Smart Thermostat

In the box:

Thermostat Mobile stand + wall bracket Relay Boiler adaptor Mains adaptor Mounting plate 5 colour adhesives 3 AAA batteries Screws / Anchoring screws	Programme Set your weekly heating programme simply by answering 5 questions. You can create as many schedules as you like.	Multi-zone You can install a thermostat for each heating circuit (e.g., ground floor and first floor). One (1) relay and one (1) additional thermostat (not included) are required for each zone. Managing all the heating zones using the same app.
Mechanics and design Designed by Starck. Translucent perspex cube. 5 interchangeable colours.	E-paper display Energy efficient, extended range capability and optimum readability.	Dimensions Thermostat: 83 x 83 x 22 mm.
Captors and measures Temperature (measure): Range: 0° C to 50° C Accuracy: +- 0.1° C Temperature (setpoint): Setpoint range: 5° C to 30° C Increment measure: 0,5° C Units: °C	Power and batteries 3 AAA batteries. Duration: two years.	Free app No subscription fees. Free access through the IBERDROLA Customers App. Compatible with iOS / Android iOS 8.0 minimum required for iPhone, iPad, iPod. Android 4.0 minimum required with access to Google Play.
Installation Compatible with gas, fuel, wood boilers and heat pumps. Replaces wired and wireless thermostats. Easy installation.	Technical features Dry contact thermostat (ON/OFF). Switching current: Max. 4 A. Switching voltage: Max. 250 VAC. Maximum switching capacity: 120 VA (4 A load @ 30 V, 1 A load @ 110 V/120 V or 0.5 A load @ 220 V/240 V).	Wireless specifications Compatible with Wi-Fi 802.11 b/g/n (2.4 GHz).

Compliance with regulations

CE